

updated:
24-Feb-10

Lilja special rimfire contours and factory rimfire contours

desig.	DESCRIPTION	blank length	blank dia.
rf 1	.990" for 4" then .875" straight	28	1
rf 2	.990" HV, 3" of .990" to .625" at 28"	28	1
rf 3	1.200" for 4" then .875" straight with radius in corner	28	1.25
rf 4	.900" for 3" then .835" dia. straight	28	1
rf 5	1.200" for 3" then .880" dia. straight	28	1.25
rf 6	1.200" dia. For 3" then 1" dia. straight	28	1.25
rf 7	1.200" dia. For 3" then .900" dia. straight	28	1.25
rf 8	1.250" for 3" then 1.125" dia. straight	28	1.25
rf 9	1.200" for 4" then 1.000" straight with radius in corner	30	1.25
rf 10	1.200" for 3" then .940" dia. straight with radius in corner	28	1.25
rf 11	1.200" for 3" then .875" straight with radius in corner	28	1.25
rf 12	1.050" for 4" then straight taper to .900" at 28"	30	1.25
rf 13	1.200" for 4" then straight taper to .825" at 28"	28	1.25
rf 14	.920" for 4" then st. taper to .725" at 24"	24	1
rf 15	.937" for 3" then st. taper to .725" at 26" (.707" at 28" , .009" / inch)	28	1
rf 16	1.075" for 3" then st. taper to .564" at 24" (.024" / inch)	24	1.25
rf 17	.815" for 4" then st. taper to .750" at 24"	24	1
rf 18	1.200" for 3" then .800" straight with radius in corner	28	1.25
rf 19	1.200" for 4" then .930" dia. straight with radius in corner	28	1.25
rf 20	1.200" for 4" then .875" dia. straight with radius in corner	30	1.25
rf 21	1.200" for 3" then .850" dia. st w/radius in corner	28	1.25
rf 22	.930" for 2.5" then st. taper to .700" at 23" (.689" at 24")	24	1
rf 23	.958" for 3.5" then .939" st. w/radius in corner	28	1
rf 24	.990" for 3" then st. taper to .750" at 27" (also same as Cooper Varmint taper)	28	1
rf 25	1.100" for 4" then st. taper to .750" at 26" (.718" at 28")	28	1.25
rf 26	.900" for 3" then st. taper to .750" at 27" (.744" at 28")	28	1
rf 27	.850" for 3" then .775" dia. straight w/radius in corner	28	1
rf 28	.940" for 4" then .900" st.	28	1
rf 29	.990" for 5" then .950" dia. st. w/radius in corner	28	1
rf 30	.950" for 5" then .890" dia. St.	28	1
rf 31	1.150" for 3" then .875" dia. St.	28	1.25
rf 32	1.150" for 13" then .900" dia. St. w/ radius in corner	28	1.25
rf 33	1.200" for 3" then .860" dia. St. w/radius in corner	28	1.25
rf 34	.985" for 3" then st. taper to .785" at 28" (29" blank)	29	1
rf 35	.850" for 5" then .790" dia. straight	28	1
rf 36	1.060" for 3" then st. taper to .875" at 27"	28	1.25
rf 37	1.250" for 3" then .750" dia. straight w/radius in corner	28	1.25
rf 38	.985" for 2.62" then .945" dia. Straight (similar to rf 104)	28	1
rf 39	.945" for 6" then .866" straight w/ radius in corner	28	1
rf 40	1.200" for 4" then .980" dia. straight with radius in corner	28	1.25
rf 41	1.100" for 4" then st. taper to .800" at 26" (.773" at 28")	28	1.25
rf 42	1.200" dia. for 4" then .850" dia. straight	28	1.25
rf 43	1.200" for 3" then st. taper to 1" at 6" then 1" dia. Straight	28	1.25
rf 44	1.200" for 2.5" then st. taper from 1.050" to .950" w/radius in corner	28	1.25
rf 45	1.200" for 5" then .815" dia. straight with radius in corner	28	1.25
rf 46	.900" for 3" then straight taper to .600" at 24" (.540" at 28")	28	1

rf 47	1.200" for 2.5" then straight taper from 1.050" to .950" at 30"	31	1.25
rf 48	1.100" for 4" then straight taper to .755" at 27" (.740" at 28", .015"/inch)	28	1.25
rf 49	1.00" for 13" then .936" dia. straight	28	1
rf 50	1.00" for 3" then taper over .5" to .770" dia. then .770" dia. to muzzle	28	1
rf 51	1.220" for 3" then taper over .5" down to .850" dia to muzzle	28	1.25
rf 52	1.060" for 3" then st. taper to .632" at 28" (.700" at 24") .017" per inch taper	28	1.25
rf 53	.970" for 3" then st. taper to .700" at 25.5" (.670" at 28" .012" per inch taper) similar to rf 83	28	1
rf 54	.975" for 3" then st. taper to .875" at 28" (.004" per inch taper)	28	1
rf 55	1.126" for 2.5" then a st. taper to .868" at 27" (.858" at 28", .010"/inch taper)	28	1.25
rf 56	.950" for 2.5" then st. taper to .825" at 26" (.815" at 28", .005"/inch)	28	1
rf 57	1.050" for 2.5" then straight taper to .850" at 30"	31	1
rf 58	1.00" for 3" then taper to .850" at 4.5" then .850" dia. straight to muzzle	28	1
rf 59	1.00" dia. 3.8" then .950" dia. straight	31	1.25
rf 60	1.00" for 5" then .900" dia. straight	28	1
rf 61	1" dia. for 3" then .825" dia. straight	28	1
rf 62	1.250" for 4" then .900" dia. straight with radius in corner	28	1.25
rf 63	1.125" for 3" then straight taper to .950" at 27" (.943" at 28")	28	1.25
rf 64	1.200" for 4" then .825" dia. straight with radius in corner	28	1.25
rf 65	.980" for 2.5" then taper over 5" length to .880" then st. taper to .750" at 24"	24	1
rf 66	1.000" for 20" then 1.200" dia. straight (shop note: run backwards)	28	1.25
rf 67	.960" for 2.5" then st. taper to .552" at 28" (.600" at 25" - .016"/inch taper)	28	1
rf 68	1.200" dia. for 4" then .800" dia. st. w/radius in corner	28	1.25
rf 69	reverse taper with both ends at .950" dia. and smallest dia. in center .700" (shop note: hold muzzle end in chuck)	28	1
rf 70	1.040" dia. for 3" taper to .875" dia. at 6" then .875" dia. st.	28	1.25
rf 71	1.000" dia. for 3" then st. taper to .710" at 28" (.011"/inch taper)	28	1
rf 72	same as rf 69 but smallest dia. is .760"	28	1
rf 73	.875" dia. for 2.5" then st. taper to .738" at 24" (.750" at 22")	24	1
rf 74	1.035" dia. for 3" then st. taper to .860" at 27" (.853" at 28")	28	1.25
rf 75	1.000" for 2.5" then .780" dia. st. with 45° chamfer in corner	24	1
rf 76	.975" for 3" then st. taper to .760" at 24" (.800" at 20") (can use for Rem 504)	24	1
rf 77	1.050" for 4" then st. taper to .900" at 28" (.882" at 30") (similar to rf 12)	31	1.25
rf 78	.995" dia. for 3" then .500" dia. st. with radius in corner	28	1
rf 79	.890" for 3.25" then st. taper to .740" over 4.75" then st. taper to .670" at 28"	28	1
rf 80	.950" for 3" then st. taper to .650" at 24" (.593" at 28")	28	1
rf 81	1.150" for 5" then .875" dia. st. with radius in corner	28	1.25
rf 82	.982" dia. for 4.5" then st. taper to .940" at 24.5" (.932" at 28")	28	1
rf 83	.985" dia. For 2.5" then st. taper to .665" at 28" (.012" per inch) similar to rf 53	28	1
rf 84	1.060" for 3" then st. taper to .815" at 28" (.785" at 31")	31	1.25
rf 85	1.085" for 6" then st. taper to .875" at 28" (.847" at 31") (BSA Martini)	31	1.25
rf 86	1.000" for 5" then taper over 1" to .940" cylinder for 17" then taper over 1" up to 1.013" for 4" (reverse taper)	28	1.25
rf 87	1.000" for 3.5" then drop to .800" dia. Then taper up to .900" over 19" then .900" to muzzle (reverse taper)	28	1
rf 88	.900" for 4" then taper over 4" to .750" then .750" to muzzle	28	1
rf 89	1.000" for 4" then taper over 1" to .850" then taper over 18.5" to .650" then taper up to 1.000" over 1.5" then 1.000" to muzzle (reverse taper)	28	1
rf 90	.791" for 5.142" then taper down to .709" dia. Straight cyl. For 17.716" then taper up to .748" dia. For 5.142" (reverse taper)	28	1
rf 91	1.00" dia. For 3" then taper over .5" to .825" dia. St. cyl for 20" then taper up to	28	1

	.5" the 1" dia. St. for 4" (reverse taper)		
rf 92	.900" dia. For 2.5" then st. taper to .735" over 6.5" then st. taper to .600" over 12" .566" dia. Muzzle at 24"	24	1
rf 93	1.250" for 3" then st taper to .825" over 3" then .825" st. to muzzle	28	1.25
rf 94	.815" for 3" then st. taper to .625" at 27" (.617" at 28")	28	1
rf 95	.950" for 9" then st. taper to .850" at 30" (.845" at 31")	31	1
rf 96	.995" for 3.5" then st. taper to .875" at 22" (.862" at 24")	24	1
rf 97	.990" for 4" then .820" dia. st with radius in corner	28	1
rf 98	.990" for 4" then .750" dia. st with radius in corner	28	1
rf 99	1.000" for 4" then st. taper to .620" at 30"	30	1
rf 100	.900" dia. cylinder with 4" of .935" dia. at muzzle end	24	1
rf 101	.875" dia. for 21" then taper up to .940" dia. over 2" then .940" st. to muzzle (reverse taper)	28	1
rf 102	1.125" for 3" then .850" dia. st. w/radius in corner	28	1.125
rf 103	.980" dia. for 2.5" then st. taper to .643" at 24"	24	1
rf 104	.992" for 3" then .950" dia. st. w/radius in corner (similar to rf 38)	28	1
rf 105	1.200" for 3" then .975" dia. st. with 45° transition	28	1.25
rf 106	same as rf 105 but 24" blank and 45° at muzzle	24	1.25
rf 107	1.170" for 5.0" the drop to 1.090" for 19" then back up to 1.170"	28	1.25
rf 108	1.25" dia. For 4" then .925" dia. St W/radius in corner	31	1.25
rf 109	.950" for 2.5" then st. taper to .650" at 30" (.640" at 31")	31	1
rf 110	.950" for 2.5" then st. taper to .672" at 28"	28	1
sund24	Sundberg taper, .900" for 5.5" then straight taper to .700" at 24"	24	1
sund26	Sundberg taper for 26" finish	26	1
sund28	Sundberg taper, .900" for 5.5" then straight taper to .660" at 28"	28	1

Anschutz

ans1710	copy of Anschutz model 1710: 1.000" for 2.75" then taper to .810" over 4" then straight taper to .654" at 28" (original .685" at 24") This contour is almost identical to the barrel used on the M. 1432 22 Hornet, (within .010" or less at any point)	28	1
ansm54m	copy of Anschutz model 54 M Sporter (original was 22 WMR) .990" dia. for 2.62" then radius over 4" to .720" dia. at tangent point then st. taper to .585" at 24" (.558" dia. at 28" blank length, blank has 3" long shank of .990" dia.)	28	1
m164	copy of Savage/Anschutz M. 164 .875" for 2.5" .661" at radius tangent, .629" at 28" (original .636" at 22")	28	1
anscsite	.923" straight with 3.8" long 1.014" diameter bulge for front site at muzzle (shop note: run backwards in lathe)	31	1.25
ans1907	.94" dia. For 2.5" then center section diameter of .885" for 21.5" then .940" dia. at muzzle for 4" (reverse taper)	28	1

Browning

brown52	Browning / Winchester model 52 contour .555" muzzle dia., .830" at radius .965" dia. shank (see also Winchester M. 52 contour below)	28	1.25
bpr22	Browning BPR 22 WMR .900" for 2.5" then st. taper to .555" (.530" at 24")	24	1
abolt22	Browning A-Bolt 22 rimfire contour .970" to .765" over 4.25" then st. taper to .610" at original muzzle length of 22", .570" at 28"	28	1

Cooper Arms

ca150	Cooper Arms CA150 barrel contour .940" for 2.5" then st. taper to .510" at 28"	28	1
rf 24	Cooper Varmint taper: .990" for 3" then st. taper to .750" at 27"	28	1

CZ			
cz527	copy of CZ model 527 .980" dia. Shank, .780" dia. At radius tangent to .570" at muzzle (original 22" fin)	24	1
Kimber			
kimber22	Kimber contour, .965" dia. Shank with .595" muzzle, .765" dia. At radius tangent	24	1
kimvrmt	Kimber varmint taper: 1.050" for 3.5" st. taper to .685" at 26" (.653" at 38")	28	1.25
kim82	.970" for 2.5" then st. taper to .600" at 23" (.525" at 28")	28	1
Remington			
504tt	Remington 504 target taper, .975" for 3" then st. taper to .600" at 21", .538" at 24"	24	1
504sport	Remington 504 copy of factory sporter contour	24	1
504remtt	Remington 504 copy of factory target taper	24	1
remttlg	Remington 504 target taper for a 28" long blank (.990" for 2.5", .800" at 28")	28	1
504lgtt	Remington 504 our target taper: .975" for 3" then st. taper to .600" at 28"	28	1
Ruger			
77vrmt	Ruger 77/22 Varmint taper, .920" to .650" at 24"	24	1
77vrmt28	Ruger 77/22 varmint taper, .920" to .600" at 28"	28	1
Rugersp	Ruger drop-in Sporter contour, turn to .510" at 24", 2.5" long shank needs to be trimmed to 2.5" long shank	24	1
ruger23	Ruger drop-in Sporter contour like rugersp for 23" blank and 2" long shank	23	1
ruger26	Ruger drop-in sporter contour like ruger23 for 26" long blank and 2.5" shank, trim .5" from shank end	26	1
ruger28	same as ruger26 but for 28" long blank	28	1
Sako			
p94sport	copy of Sako P94 Finfire & Quad Sporter contour (.575" at 24")	24	1
Weatherby			
mkxxll	Copy of Weatherby/Anschutz model Mark XXII 17 HMR barrel .875" dia. at chamber st. taper to .750" over 2.5" then st. taper to muzzle dia. of .630" at 23"	24	1
Winchester			
win52	Winchester M. 52 contour w/ 1.010" shank to .520" at 28", .690" at radius tangent (see also Browning M. 52 contour above)	28	1.25
win52t	Win M. 52 Target taper: 1.030" for 2.5" then st. taper to .880" then st. taper to .725" at 28" (will make finish barrel length up to 26")	28	1.25
52tt	1.010" for 2.5" then st. taper to .875" at 28"	28	1.25

To order any of these contours use our designation at left.

[We can program for special tapers not listed here for a one-time \\$30 charge.](#)