

updated:
28-Aug-08

Lilja 15" long XP-100 type contours

Igth.

Designation

Specifications:

xp 1	1.200 for 2.5" then st. taper to .625" at 15"	15
xp 2	1.200" for 2.7" then st. taper to .825" at 4.7" then .825" st. to 15"	15
xp 3	1.250" for 2.25" the st. taper to .900" at 3.40" then st. taper to muzzle of .620"	15
xp 4	1.200" for 2.5" then 20" radius down to .680" at 5.50" then st. taper to .600" at 15"	15
xp 5	1.200" for 3" then 30" radius down to .800" at 6.00" then st. taper to .725" at 15"	15
xp 6	1.250: for 2.6" then 30" radius down to .900" at 4.50" then .900" st. out to muzzle at 15"	15
xp 7	1.200" for 2.5" then 20" radius down to .680" at 5.50" then st. to .680" at 15"	15
xp 8	1.200" for 2.5" then 24" radius down to .825" at 5.5" then st taper to .750" at 15"	15
xp 9	1.200" for 2.5" then st. taper to .650" at 15" (very similar to xp 1)	15
xp 10	copy of Savage model 516 contour except shank dia. is 1.065" for 2.5" and OAL is 15" muzzle dia. is .725" (original Savage was 12.3" OAL)	15
xp 11	1.200" for 2.5", .725" at radius tangent and .640" at 15" (similar to Remington contour)	15
xp 12	1.250" for 2.5" then st. taper to .800" at 15"	15
xp12-20	same as xp 12 but with 20" finish length, .800" at 20"	20
xp 13	1.350" for 2.5" then 30" radius down to .900" at 5.5" then st. taper to .800" at 15"	15
xp 14	1.200" for 2.5" then taper to .855" over 1" then st. taper to .575" at 15" very similar to Remington 7 BR contour but longer on 1.200" dia.	15
tc 1	1.00" for 2.5" then radius down to .750" over 4" then st. to .750" dia. muzzle	15
xphtr	1.200" for 3" then st. taper to 1.000" at 15"	15

To place an order for any one of these contours use our designation in the left column.
[We can program for special tapers not listed here for a one-time \\$30 charge.](#)